

Door and Window System



MVT67 MVT77

Hidden Vent

It provides sash application possibility
which is invisible from the outside.



MVT67 - MVT 77 Hidden Vent Door & Window System

TECHNICAL PROPERTIES

	MVT67	MVT77
Frame Width	67 mm	77 mm
Sash Width	69 mm	78,5 mm
Thermal Break	24 mm	34 mm
Profile Wall Thickness	2 mm	2 mm
Min. Glazing Thickness	14 mm	24 mm
Max. Glazing Thickness	26 mm	36 mm
Min. Sash Dimensions	350 x 700 mm	350 x 700 mm
Max. Sash Dimensions	1300 x 2800 mm	1300 x 2800 mm
Max. Sash Weight	130 kg	130 kg

PERFORMANCE VALUES

Air Permability	Class 4 (600 Pa)	Class 4 (600 Pa)
Water Tightness	Class 9A (600 Pa)	Class 9A (600 Pa)
Wind Resistance	Class C4 (1800 Pa)	Class C4 (1800 Pa)
Min. Thermal Insulation	Uf: 2,20-2,37 W/(m ² .K)	Uf: 1,8-2,08 W/(m ² .K)

APPLICATION OPTIONS

Inward Opening Sash	✓	✓
Outward Opening Sash	✗	✗
Tilt and Turn Opening	✓	✓
Transom Opening	✓	✓
Double Sash Opening	✓	✓
Pivot Opening	✓	✓

